

Manual equipment tester for static tests on full-face masks and lung-governed demand valves

Data recording by means of a pressure gauge



Multitest Pult ND offers the same features and functionality as the Multitest ND equipment tester. With just four controls, it allows you to carry out all of the static tests that need to be performed on full-face masks and lung-governed demand valves (LGDV) in an efficient and equally convenient manner.

The tester has a round-thread equipment port. Thanks to a broad range of optional adapters (see accessories), it is also possible to test a wide variety of equipment with other connector/port types from a large number of manufacturers.

The required levels of positive and negative pressure as well as the necessary flow rates for opening-pressure tests and closing-pressure tests are supplied by the built-in pump.

The pressure gauge has a diameter of 100 mm and a finely graduated scale, making it easy to take pressure readings with perfect accuracy. Moreover, there is a zero-offset calibration screw. Lung-governed demand valves are connected to the equipment port for testing, while masks with five-point head harnesses are strapped onto the inflatable dummy head. The head, which comes with a clamp for fastening it to a table or a workbench, ensures that the masks sit properly on a human-like face during testing. In combination with optional accessories, the tester can also be used for testing many makes and models of two-point helmet masks. Multitest ND Pult is powered by a 1.5-V battery (D cell) (included in the scope of delivery).

Possible tests

- ❖ full-face masks – leak test
- ❖ full-face masks – opening pressure
- ❖ lung-governed demand valves – leak test
- ❖ lung-governed demand valves – opening pressure
- ❖ lung-governed demand valves – closing pressure

The following tests require optional accessories:

- ❖ chemical protective suits – leak test
- ❖ chemical protective suits – leak test of the suit valves

Scope of delivery

- ❖ Multitest ND Pult
- ❖ dummy head (incl. filling valve and clamp)
- ❖ mask testing hose (round thread)
- ❖ sealing plug for the LGDV hose
- ❖ silicone spray
- ❖ timer
- ❖ 1.5-V battery (D cell)
- ❖ operating instructions

Specifications

- ❖ dimensions (w × d × h).....420 × 400 × 220 mm
- ❖ housingtexture-painted aluminium
- ❖ weight..... approx. 8 kg
- ❖ power supply 1.5-V battery (D cell)
- ❖ low-pressure gauge..... ±30 mbar¹ (cl. 1.6)
- ❖ equipment port round thread (EN 148-1)

¹) Units for international markets. Units for the Austrian market come with a ±20 mbar low-pressure gauge.

Other available models

- ❖ Multitest ND Pult N.....**330-306**
 mains-operated only
 power adapter (230/24 V) included

Please note: Optional accessories are sold separately.



LGDV connected to equipment port

Errors and omissions excepted! Technical specifications subject to change without notice!



Accessories and other products

Mask testing adapters



MSA plug-in connector	330-048
MSA AutoMaXX	330-152
Threaded connector M45x3	330-050
Dräger plug-in connector	330-049
Interspiro plug-in connector	330-051
Interspiro Click	330-168
Interspiro Inspire	330-496
Plug-in connector ESA	330-178
Round-thread connector	330-471

LGDV testing adapters



MSA plug-in connector	330-011
MSA AutoMaXX	330-149
Threaded connector M45x3	330-012
Dräger plug-in connector	330-013
Interspiro plug-in connector	330-014
Interspiro Click	330-162
Interspiro Inspire	330-498
Plug-in connector ESA	330-175

Kit for testing chemical protective suits



Filling hose and testing hose for performing leak tests on chemical protective suits. Valve tester, complete with an expansion tank, for leak testing the exhalation valves.

for MSA suits	330-583
for Dräger suits	330-584
for Interspiro suits	330-585

Accessories for testing two-point helmet masks



Helmet-mask holder – standard model	330-233
Adapters (MSA Avon/Schuberth) for art. no. 330-233	330-127
Adapters (Interspiro Heros) for art. no. 330-233	330-128
Helmet-mask holder for installation on dummy head (for Dräger/MSA masks)	330-210
Helmet-mask holder for installation on dummy head (for Interspiro masks)	330-522

Other accessories



Protective hood for dummy head	340-001
Silicone spray	330-470
Sealing plug for lung-governed demand valve	330-526
Sealing plug for testing hose	220-401

Software

Please do not hesitate to get in touch with us if you have any questions or if you would like to learn more about the functionality of our software products, their range of possible applications and their use on computer networks.

Equipment management program (V5, excl. cylinder filling functionality)	330-453
Program option for managing any kind of equipment	330-448
Program option for carrying out/managing cylinder fillings	330-341

Barcode



Barcode scanner, wired (USB)	330-154
Barcode scanner, wireless (incl. USB cradle and power adapter)	330-221
Barcode labels, adhesive front (pack of 100)	330-220
Barcode labels, adhesive back (pack of 100)	330-219

RDT 09 mask washing machine



For cleaning, disinfecting and drying up to 9 respiratory protective masks in 4 hours (an adapter for processing up to 9 LGDVs at the same time is sold separately). The PLC-controlled machine operates fully automatically and adds the required amount of disinfectant all by itself. The concentration level is freely adjustable from 0.2% to 2%. A warm-air blower is used for drying the masks at a maximum of 50 °C.

Errors and omissions excepted! Technical specifications subject to change without notice!

